



TECHNICAL DETAILS
“SULZER” COOLING TOWER EWK-D (A)

Cooling tower standard model	Water flow-rate in m ³ /h		Rated cooling capacity in kW for 35 °C/29.5°C at t _{wb}			Motor rating kW	Dimensions in mm			Weight in kg	
	min	max	22 °C	24°C	26°C		length	width	height	dry	operating/ max
EWK-D											
144/09	7	45	248	206	159	4.0	2510	1310	2603	550	1200/1500
225/09	11	70	372	308	241	5.5	3000	1620	2603	730	1750/2200
324/09	16	100	565	470	371	7.5	3500	1900	2603	880	2500/3100
450/09	20	135	768	641	502	11.0	3970	2140	2655	950	3000/3600
680/09	34	200	1156	972	762	15.0	5116	2280	2690	1700	4300/5500
930/09	45	280	1607	1346	1054	22.0	6328	2280	2690	2300	5500/7800

Cooling tower standard model	Water flow-rate in m ³ /h		Rated cooling capacity in kW for 35 °C/29.5°C at t _{wb}			Motor rating kW	Dimensions in mm			Weight in kg	
	min	max	22 °C	24°C	26°C		length	width	height	dry	operating/ max
EWK-DA											
144/09	7	45	248	206	159	5.5	3800	1310	3533	950	1660/1960
225/09	11	70	372	308	241	7.5	4150	1620	3533	1300	2360/2810
324/09	16	100	565	470	371	15.0	4700	1900	3533	1730	3330/3930
450/09	20	135	768	641	502	22.0	5120	2140	3700	1700	3900/4500
680/09	34	200	1156	972	762	30.0	6266	2280	4035	2750	5710/6910
930/09	45	280	1607	1346	1054	37.0	7541	2280	4035	3550	7030/9330

Subject to modification without notification.